


PRESMALL

*full electric
machine*



La vera mini pressa ad iniezione da tavolo

The real injection bench mini-press

Die echte Tisch-Minispritzgussmaschine

La verdadera mini maquina de inyeccion de mesa

La vrai mini-presse à injection de table


presma

PRESMALL


Iniezione	Injection	Spritzeinheit	Inyección	Injection		
diametro vite	screw diameter	Schneckendurchmesser	diametro del tornillo	diamètre vis	mm	14 - 16 - 18
rapporto vite L/D	L/D ratio	L/D Verhältnis	relación L/D	rapport L/D vis	L/D	20 - 18 - 16
velocità rotazione vite	screw r.p.m.	Schneckenumdrehungen	revoluciones max. del tornillo	vitesse rotation vis	rpm	10÷200
pressione max. d'iniezione	max injection pressure	Einspritzdruck	presión de inyección	pression d'injection	kg/cm ²	2400-1900-1490
corsa iniezione	injection stroke	Einspritzhub	carrera del tornillo	course d'injection	mm	90
volume teor. iniezione	theor. injection capacity	Theor. Spritzkapazität	volumen teor. de inyección	capacité injection theor.	cm ³	13 - 18 - 22
capacità iniezione (PS)	real injection capacity (PS)	Reelle Spritzkapazität (PS)	capacidad de inyección (PS)	capacité injection réelle (PS)	g	12 - 15 - 19
zone termoregolate	heating zones	Heizonen	zonas de calefacción del cilindro	zones chauffe fourreau	n°	3+1
potenza riscaldamento	installed heating power	Installierte Heizungskraft	potencia de calefacción	puissance chauffage	kW	1,6

Chiusura	Clamping	Schließeinheit	Cierre	Fermeture		
forza chiusura stampo	clamping force	Schliesskraft	fuerza de cierre	force de fermeture moule	kN	58
corsa apertura stampo	opening stroke	Öffnunghub	recorrido de abertura	course d'ouverture moule	mm	80
spessore stampo minimo	min. mould thickness	Min. Formhöhe	altura minima del molde	min. épaisseur moule	mm	100
distanza max tra i piani	daylight	Max. Abst. zwischen den Platten	distanza maxima entre platos	max. distance entre plateaux	mm	140
passaggio colonne	distance between columns	Licht zwischen den Holmen	distanza entre columnas	passage entre colonnes	mm	120x120
corsa estrattore	ejection stroke	Auswerferhub	recorrido de expulsión	course extracteur	mm	50

Dati generali	General data	Allgemeine Daten	Datos generales	Caractéristiques générales		
potenza totale installata	total installed power	Installierte Gesamtkraft	potencia total conectada	puissance totale installée	kW	11,6
potenza media assorbita	absorbed power	Aufgenommene Leistung	potencia absorbida	puissance absorbée	kW	1,2
dimensioni pressa	machine dimensions	Maschinenabmessungen	dimensiones de la inyectora	encombrement presse	mm	1900x750x800
peso pressa	machine weight	Gewicht	peso de la inyectora	poids presse	kg	350



Display Touch Screen
Touch Screen display
Touch-Screen Bildschirm
Pantalla Touch Screen
Ecran tactile



Gruppo chiusura
Clamping unit
Schließeinheit
Grupo de cierre
Unité de fermeture



Gruppo iniezione
Injection unit
Spritzeinheit
Grupo inyección
Unité d'injection



presma
SPA
Injection Moulding Machines

Via delle industrie, 8/10
21040 Torba di Gornate Olona (VA) Italy
Tel. +39 0331811611
Fax +39 0331820026
e-mail: info@presma.it - www.presma.it

**Non Standard
Technology**
for Thermoplastics and Rubber